

PATENT ABSTRACTS OF JAPAN

(11)Publication number : **57-117333**
(43)Date of publication of application : **21.07.1982**

(51)Int.Cl. **B01J 8/24**
B01J 35/08
// B01D 53/36

(21)Application number :	56-003816	(71)Applicant :	GADELIUS KK
(22)Date of filing :	16.01.1981	(72)Inventor :	OKAMOTO EIJI FUKAYA YASUHIRO YAMADA TAKATOSHI

(54) REACTION APPARATUS FLUIDIZED LAYER TYPE CATALYTIC GAS

(57)Abstract:

PURPOSE: To carry out gas-solid contact in good efficiency by using a catalyst with reduced pressure loss and a large specific surface area by fluidizing the catalyst with a particle size in a specific range on a porous plate and upto a specific height.

CONSTITUTION: In the fluidized layer type catalytic gas reaction apparatus, a granular catalyst 5 with a particle size of 0.2mmW2mm is held on a porous plate 3 and the layer of the catalyst 5 is fluidized by a gas stream 2 but the height of the formed fluidized layer is adjusted to 300mm or less. In this manner, because the catalyst with a large specific surface area and reduced pressure loss is used and the height of the fluidized layer is low gas-solid reaction efficiency is high, even if the amount of the catalyst to be used is small.

